



SafeCoin D 700

Wall-mounted self-service coin roll dispenser for banks and retail

The SafeCoin D family of machines sets a new standard for coin roll dispensers. SafeCoin D 700 is a compact self-service solution with colour screen and softkeys for around-the-clock dispensing of coin rolls.

The machine accepts banknotes and coins and exchanges them for coin rolls, coins or notes of another denomination. It can store between 200-525 coin rolls per module and between 1000-2000 coins per hopper. In order to meet the

demands that 24-hour-a-day service requires, SafeCoin D 700 is built using only the latest and most reliable components.

Configuration of the terminal is flexible to allow clients to choose a machine which suits their own particular requirements. The client can select the required functions and components from the configuration options available.

SafeCoin D 700

Wall-mounted self-service coin roll dispenser for banks and retail

Design

Depending on requirements, SafeCoin D 700 can be installed as a through-the-wall or in-the-wall unit. The machine can be accessed from the rear, making it easy for staff or CIT companies to empty or fill and for technicians to service.

To make each transaction quick and simple for the end user, a colour screen and softkeys guides the customer through the process.

Management Software

SafeControl is an innovative web-based solution for the monitoring and administration of your complete self-service network. Designed for use with SafeCoin and other Gunnebo self-service machines to give a real-time overview of the status and performance of all terminals across your entire operation.

Exchange Options

- Banknotes to coin rolls
- Banknotes to coins
- Coins to coins
- Banknote to banknotes (smaller denominations)

Capacity

Coin rolls (a double roll dispenser has two modules)

per module	e.g. 2 EUR	200 coin rolls
(depending on value)	e.g. 0.10 EUR roll	350 coin rolls

individual coins		
per coin hopper	e.g. 2 EUR	1000 coins
(depending on value)	e.g. 0.10 EUR	2000 coins

Technical Data

Positioning:	Wall-mounted (TTW, ITW)
Placement:	Indoor
Servicing:	Rear-loading
Supply voltage:	AC 230 V \pm 10%
Mains frequency:	50Hz
Power consumption:	100 VA standby 200 VA transaction
Dimensions (WxHxD in mm):	760x1750x1015
Service area behind the machine (WxD in mm):	1500x1200
Weight (empty/full):	480/1160kg
Material:	3mm steel housing and door
Ambient temperature:	+5 °C to +45 °C
Relative humidity:	20% to 80% (non-condensing)
Paint colour:	Special RAL 9006 and 9007 powder coating. Other RAL colours on request.

Features

- 24/7 self-service
- High-capacity coin roll dispensing modules
- High degree of operational reliability
- Four functions in one machine
- Control of individual components using CAN bus technology
- Windows XP operating system
- Electronic log
- Connection to the bank's network
- Monitoring

End User Benefits

- Self-service machine
- Shorter waiting times
- Around-the-clock availability
- Customer identification by means of a card reader (user option)
- Several services in one device: rolls, coins, banknotes
- Various fee models available

We reserve the right to alter product information without any obligation.

