



SafeCoin D 700F

Freestanding self-service coin roll dispenser for banks and retail

The SafeCoin D family of machines sets a new standard for coin roll dispensers. SafeCoin D 700 F is a compact self-service solution with colour touch screen for around-the-clock dispensing of coin rolls.

The machine accepts banknotes and coins and exchanges them for coin rolls or coins of another denomination. It can store between 180-470 coin rolls per module and between

1100-2000 coins per hopper. In order to meet the demands that 24-hour-a-day service requires, SafeCoin D 700 F is built using only the latest and most reliable components.

Configuration of the terminal is flexible to allow clients to choose a machine which suits their own particular requirements. The client can select the required functions and components from the configuration options available.

SafeCoin D 700F

Freestanding self-service coin roll dispenser for banks and retail

Design

SafeCoin D 700 F can be installed as a freestanding unit. The machine can be accessed from the front, making it easy for staff or CIT companies to empty or fill and for technicians to service.

To make each transaction quick and simple for the end user, a colour touch screen guides the customer through the process.

Management Software

SafeControl is an innovative web-based solution for the monitoring and administration of your complete self-service network. Designed for use with SafeCoin and other Gunnebo self-service machines to give a real-time overview of the status and performance of all terminals across your entire operation.

Exchange Options

- Banknotes to coin rolls
- Banknotes to coins
- Coins to coins

Capacity

Coin rolls (a double roll dispenser has two modules)

| | | |
|----------------------|--------------------|----------------|
| per module | e.g. 2 EUR | 180 coin rolls |
| (depending on value) | e.g. 0.10 EUR roll | 310 coin rolls |

| | | |
|----------------------|---------------|------------|
| individual coins | | |
| per coin hopper | e.g. 2 EUR | 1100 coins |
| (depending on value) | e.g. 0.10 EUR | 2000 coins |

Technical Data

| | |
|---------------------------|---|
| Positioning: | Freestanding |
| Placement: | Indoor |
| Servicing: | Front-loading |
| Supply voltage: | AC 230 V \pm 10% |
| Mains frequency: | 50Hz |
| Power consumption: | 100 VA standby 200 VA transaction |
| Dimensions (WxHxD in mm): | 790x850x1570 |
| Weight (empty/full): | 450/1250kg |
| Material: | 3mm steel housing and door |
| Ambient temperature: | +5 °C to +45 °C |
| Relative humidity: | 20% to 80% (non-condensing) |
| Paint colour: | Special RAL 9006 and 9007 powder coating. Other RAL colours on request. |

Features

- 24/7 self-service
- High-capacity coin roll dispensing modules
- High degree of operational reliability
- Four functions in one machine
- Control of individual components using CAN bus technology
- Windows XP operating system
- Electronic log
- Connection to the bank's network
- Monitoring

End User Benefits

- Self-service machine
- Shorter waiting times
- Around-the-clock availability
- Customer identification by means of a card reader (user option)
- Several services in one device: rolls, coins, banknotes
- Various fee models available

We reserve the right to alter product information without any obligation.

