



SafeCoin D 900

Self-service banknote, coin and coin roll exchange for banks and retail

The SafeCoin D family of machines sets a new standard for coin roll dispensers. SafeCoin D 900 is a compact self-service solution with colour touch screen for around-the-clock dispensing of coin rolls.

The machine exchanges banknotes for coin rolls or coins and exchanges coins for banknotes or coins of another denomination. It can store between 200-525 coinrolls, 1000-2000 coins per hopper and between 1500-2500 notes

per cassette. In order to meet the demands that 24-hour-a-day service requires, SafeCoin D 900 is built using only the latest and most reliable components.

Configuration of the terminal is flexible to allow clients to choose a machine which suits their own particular requirements. The client can select the required functions and components from the configuration options available.

SafeCoin D 900

Self-service banknote, coin and coin roll exchange for banks and retail

Design

SafeCoin D 900 can be installed as a Through The Wall (TTW) or In The Wall (ITW) unit. The machine is accessed from the rear, making it easy for staff or CIT companies to empty or fill and for technicians to service.

To make each transaction quick and simple for the end user, a colour screen guides the customer through the process.

Management Software

SafeControl is an innovative web-based solution for the monitoring and administration of your complete self-service network. Designed for use with SafeCoin and other Gunnebo self-service machines to give a real-time overview of the status and performance of all terminals across your entire operation.

Exchange Options

- Banknotes to coin rolls
- Banknotes to coins
- Coins to coins
- Banknote to banknotes (smaller denominations)

Capacity

Coin rolls (a double roll dispenser has two modules)

per module	e.g. 2 EUR	200 coin rolls
(depending on value)	e.g. 0.10 EUR roll	350 coin rolls

individual coins		
per coin hopper	e.g. 2 EUR	1000 coins
(depending on value)	e.g. 0.10 EUR	2000 coins

Technical Data

Positioning:	TTW/ITW
Placement:	Indoor
Servicing:	Rear-loading
Supply voltage:	AC 230 V \pm 10%
Mains frequency:	50Hz
Power consumption:	100 VA standby 200 VA transaction
Dimensions (WxHxD in mm):	960x1750x1015
Service area behind the machine (WxD in mm):	1500x1200
Weight (empty/full):	570/1350kg
Material:	3mm steel housing and door
Ambient temperature:	+5 °C to +45 °C
Relative humidity:	20% to 80% (non-condensing)
Paint colour:	Special RAL 9006 and 9007 powder coating. Other RAL colours on request.

Features

- 24/7 self-service
- High-capacity coin roll dispensing modules
- High degree of operational reliability
- Four functions in one machine
- Control of individual components using CAN bus technology
- Windows XP operating system
- Electronic log
- Connection to the bank's network
- Monitoring

End User Benefits

- Self-service machine
- Shorter waiting times
- Around-the-clock availability
- Customer identification by means of a card reader (user option)
- Several services in one device: rolls, coins, banknotes
- Various fee models available

We reserve the right to alter product information without any obligation.

